

cobra 3300W

12 V-DC ELECTRO HYDRAULIC CRANES 11,500 FT. LBS.

STANDARD FEATURES

- Engineered for 12 - 15 years of service*
- High strength hexagonal Swedish steel boom
- Boom Extension 1 Hydraulic / 1 Manual
- Worm gear rotation system
- HD 12 V-DC power pack
- Planetary electric winch
- Load limiting device
- Remote control - wireless and/or wired
- Emergency manual controls
- 2 part block
- Painted Cobra white with polyurethane enamel
- 6 Standard Operator Safety and Crane Protection Devices
 - Overload Protection on all Functions
 - Counter Balance Valves on all Cylinders
 - Main Relief Valve
 - Anti Two-Block
 - Low Boom Angle
 - Low Cable on Winch Drum



* Cobra crane structures are designed for a normal working life of 12 to 15 years according to the DIN Standard 15018 classification H2-B3.

TECHNICAL DATA

- Crane rating 11,500 ft. lbs.
- Horizontal reach 15'
- Elevation angle -5 to +80 degrees
- Slewing angle 400°
- Winch capacity, bare drum 1,650 lbs.
- Winch speed, 3rd layer 22 fpm
- Wire rope, non-rotating 82 ft of 1/4"
- Crane weight 495 lbs.

LIFTING CAPACITIES

FT.	LBS.	FT.	LBS.
3	3300	12	950
4	2870	13	880
5	2300	14	820
6	1910	15	750
7	1640		
8	1430		
9	1270		
10	1150		
11	1040		

OPTIONS / ACCESSORIES

- Outriggers - manual or hydraulic

